



## China Lm8uu Bearing Supplier



### High Precision Long Life Deep Groove Ball Bearing NSK 6206 ZZ 2RS Bearing

Bearing No. 6206

6206 Bearing 2D drawings and 3D CAD models

Size	30x62x16 mm
Bore Diameter	30 mm
Outer Diameter	62 mm
Width	16 mm
d	30 mm
D	62 mm
B	16 mm
C	16 mm
r min.	1 mm
da min.	35 mm
da max	38,5 mm
Da max.	57 mm
ra max.	1 mm
Weight	0,199 Kg
Basic dynamic load rating (C)	19,5 kN
Basic static load rating (C0)	11,3 kN
(Grease) Lubrication Speed	11 000 r/min
(Oil) Lubrication Speed	13 000 r/min
Category	Single Row Ball Bearings
Inventory	32.0
Manufacturer Name	NSK
Minimum Buy Quantity	N/A
Weight / Kilogram	0.199
EAN	0029176014444
Product Group	B00308



## China Lm8uu Bearing Supplier

Enclosure	Open
Precision Class	ABEC 1   ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch - Metric	Metric
Long Description	30MM Bore; 62MM Outside Diameter; 16MM Outer Race Diameter; Open; Ball Bearing; ABEC 1   ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Category	Single Row Ball Bearing
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer URL	<a href="http://www.nskamericas.com">http://www.nskamericas.com</a>
Manufacturer Item Number	6206
Weight / LBS	0.44
Outside Diameter	2.441 Inch   62 Millimeter
Outer Race Width	0.63 Inch   16 Millimeter
Bore	1.181 Inch   30 Millimeter
bore diameter:	30 mm
closure type:	Open
outside diameter:	62 mm
internal clearance:	Normal Clearance
overall width:	16 mm
manufacturer upc number:	029176014444



## China Lm8uu Bearing Supplier

bore type:	Round
SRI	4.81
hidYobi	6206
LangID	1
D_	62
SREX	0.04
B_	16
da min	35
hidTable	ecat_NSRDGB
Oil rpm	13000
SRE	5
mass	0.199
GRS rpm	11000
ra	1
SRIX	0.02
D_a	57
SRIN	0
C0	11.3
fo	13.8
SREN	0
DE_	56.025
Prod_Type3	DGBB_SR_OT
DA_	9.525
bomp	0
Z_	9
yobi	6206
C_conv	19500
ALPHA_	0
SDM_	46.5
r	1
KBRG	6101
SBRG	2



## China Lm8uu Bearing Supplier

DI_	36.975
-----	--------